

WIRELESS COMMUNICATION EQUIPMENT

Publication number: JP2001333080 (A)

Publication date: 2001-11-30

Inventor(s): YAMAMOTO YUKIHIRO

Applicant(s): TOYOTA IND CORP

Classification:

- International: H04B1/707; H04J13/04; H04L12/28; H04L29/06; H04B1/707;
H04J13/02; H04L12/28; H04L29/06; (IPC1-7): H04L12/28;
H04B1/707; H04L29/06

- European:

Application number: JP20000153517 20000524

Priority number(s): JP20000153517 20000524

Also published as:

JP3757758 (B2)

Abstract of JP 2001333080 (A)

PROBLEM TO BE SOLVED: To provide a wireless communication equipment the MAC(Medium Access Control) protocol of which a set-maker can freely set and that can surely receive data without the need for special operations. **SOLUTION:** Data are inserted to a MAC data unit area (MPDU) of a packet transmitted by the wireless communication equipment and data length information denoting the length of the data is inserted to a header of the packet. Upon the receipt of a packet, the wireless communication equipment sets a data reception processing time corresponding to the data length information to conduct data reception and reaches a reception standby state when the data reception time elapses. The wireless communication equipment sets a value denoting an infinite time to the data length information at the transmission of user data and sets a prescribed time to the data length information at the ID transmission by an automatic dialing function or the like. Thus, the MAC protocol such as a maximum data length and a maximum data reception processing time can freely be set. Furthermore, even in the case of receiving an ID, since the wireless communication equipment restores a reception standby state after a prescribed time, the wireless communication equipment can surely receive user data or the like.



Data supplied from the esp@cenet database — Worldwide